



ALPINE™

VINYL-FACED CEILING PANELS



A 10mm, vinyl faced ceiling tile suited to a wide range of applications. Its vinyl face makes for simple cleaning, and ensures durability and longevity; as well as reducing mould growth.

APPLICATIONS:

- Offices
- Classrooms
- Hospitality areas
- Retail areas



GROUP 1



RH 99



CLEANABLE




ANTI-MOULD

SHORT SPECIFICATION

Ceiling shall comprise NCS Alpine™ vinyl ceiling panels with NCS GT Ultimate™ 24mm steel exposed grid including wall trim as manufactured for NCS.


Panels shall be nominal size 1200 × 600 × 10mm, square (SQ) edge detail.

TECHNICAL INFORMATION

EDGE	PANEL SIZE	ITEM NO.	COLOUR	GRID	VOC EMISSIONS
SQ 	1200 × 600 × 10mm	NV1260S	White	A	Low

GRID PROFILE

A



WEIGHT

6.25kg/m²

ENVIRONMENTAL LIMITATIONS

49°C, 99% RH max.

MAINTENANCE

Can be cleaned easily with a soft brush or vacuum.

INSTALLATION

Do not begin installing until the building is fully enclosed, dry and watertight; and suitable permanent heating and cooling equipment is in operation. Ensure residual moisture from wet trades has been removed, and the area is free of fumes. Do not mix batches in a continuous area.

PROPRIETARY TECHNOLOGY

This product's combination of sag resistance and acoustic performance results from proprietary technology.

FIRE RATING

Group 1 material.

CLEANING RECOMMENDATIONS

To clean, use a clean cloth, dampened with water or a mild detergent. Wipe surface. To disinfect, spray lightly with a disinfectant solution and wipe clean with a clean cloth. Suitable disinfectants include:

- Hydrogen peroxide
- Isopropyl alcohol
- Quaternary ammonium
- Sodium hypochlorite